

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2144-5)

Set a basalt stone, 16x12x6 ins., 11 ins., in the ground, marked with 1 notch on the S. and 2 notches on the E edge, for cor. to secs. 26, 27, 34, & 35, from which

- A Fir, 7" dia. bears S.20°E. 26 lks. mkd: T23S R1W S35 BT.
- A Hemlock, 6" dia., bears N.50°W., 13 lks., mkd: T23S R1W S26 BT.
- A Fir, 6" dia. bears S.6°W., 25 lks. mkd: T23S R1W S34 BT.
- A Sugar Pine, 18" dia., bears N.85°W., 11 lks., mkd: T23S R1W S27 BT.

BLM Dependent resurvey by Harold Corbin, Cadastral Surveyor, under Group # 345 & 350, surveyed April/Oct. 1960 - (DCSO records Vol. 31 Page(s) 12967-8)

The corner of secs. 26, 27, 34, & 35, monumented with the orig. basalt stone, 16x12x6 ins., firmly set, 6" above the ground, with 1 notch on the S. and 2 notches on the E edge, from which the OBTs:

- A Hemlock, 19" dia., bears N.58½°E., 13 lks., with healed blaze. (Rec. bearing, N.50°E.)
- A Fir, 12" dia., bears S.20°E., 26 lks., with scribe marks 23S 35 visible on opened blaze.
- A Fir, 10" dia., bears S.9¼°W., 22 lks., with illegible scribe mks. visible on opened blaze. (Rec. bearing & dist., S.6°W., 25 lks.)
- A Sugar Pine, 22" dia., bears N.70½°W., 11 lks., with scribe mks. T2 R visible on partially opened blaze. (Rec. bearing, N.85°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, & set in a mound of stone, 2½ ft. base to top, with brass cap marked:

	T23S	R1W
	<u>S 27</u>	<u>S 26</u>
_____	S 34	S 35
	1960	

from which

- A Fir, 10" dia., bears S.37°E., 51 lks., mkd: T23S R1W S35 BT.
- A Fir, 10" dia., bears S.28°W., 23 lks., mkd: T23S R1W S34 BT.

Deposit orig. corner stone alongside iron post.

continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23389-23390)

The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, in a collar of stone, with a brass cap (properly) mkd. from which the remains of the original bearing trees reported by Corbin in 1960

A fir, 27" dia., bears N.58½°E., 8.6 ft., with a healed blaze. (Record, hemlock)

A hemlock, 16" dia., bears S.20°E., 15.5 ft., with a healed blaze. (Record, fir, 17.2 ft.)

A fir snag, 8" dia., 6 ft. tall, bears S.9¼°W., 14.5 ft., with a healed blaze.

A pine snag, 22" dia., bears N.70½°W., 7.3 ft., with illegible scribe marks visible on an open blaze.

and the bearing trees mkd. by Corbin

A fir, 11" dia., bears S.37°E., 33.7 ft., with a healed blaze.

A fir, 12" dia., bears S.28°W., 15.2 ft., with a healed blaze.

and a new bearing tree

A fir, 19" dia., bears N.9½°W., 18.3 ft., mkd. T23S R1W S27 BT.

The geographic position in NAD 1983 (2011)

Latitude: 43°32'13.97"N. Longitude: 122°46'55.07"W.