

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias	Description

A 27" hemlock "CSBT" bears S.60°18'E., @ 12.86' to nail, 14.0' to center. Set a pink "DEEP-1" magnet ±1' deep on line & 7.5' from the corner.
A 24" hemlock "CSBT" bears N.51°51'W., @ 31.03' to nail, 32.1' to center. Set an orange "DEEP-1" magnet ±1' deep on line & 22.9' from the corner.
Note - Distance to nail refers to a mag nail & brass washer driven into the bottom of the face of new BTs, or near the base of tree facing corner in FD BTs.
Geographic Map Location, use for navigation to corner area - Not of survey grade Accuracy
Latitude: N.43°32'37.7" Longitude: W.122°46'52.0" NAD 83/91

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23390)

The ¼ sec. cor. of secs. 26 & 27, perpetuated by Robinson, in 2003, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, in a collar of stone, with a brass cap (properly) mkd.
from which the remaining original bearing tree
A hemlock, 28" dia., bears S.57°W., 11.9 ft., with a healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.
and the bearing trees mkd. by Robinson
A hemlock, 12" dia., bears N.47¾°E., 39.2 ft., with scribe marks BT visible on a partially healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.
A hemlock, 29" dia., bears S.60¾°E., 14.6 ft., with scribe marks CS BT visible on a partially healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.
A hemlock, 26" dia., bears N.52¼°W., 32.3 ft., with a healed blaze and a Mag-Nail and washer driven into the face at the base of the blaze.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.