

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; S 2, T24-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2138)

Set basalt stone 18x14x12 ins., 12" in the ground mkd. ¼ on N. face, for ¼ sec. cor., from which

 A Fir 7" dia., bears N.75°E., 31 lks. dist. mkd. ¼ S BT.

 A Fir 8" dia., bears S.44°W., 25 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April 17, 1970 - C.S. File 54/27-204

Found - Old corner stone, as called for, mkd. ¼.

 Orig. 7" now 30" Fir, alive, N.75°E., 20.5 ft., injury over the old scar. We rescribe "¼ S35 CS BT"

 Orig. 8" now 32" Fir, alive, S.44°W., 16.5 ft., shows good scar. We rescribe "¼ S2 CS BT"

Set Brass cap at cor. mkd: County Surveyors Office

 T23S R1W ¼ S 32

 T24S S 5

 1970

Reset old stone alongside.
Corner lies 430 ft. E. of top of spur ridge, sloping SW. and approx. 1000 ft. W. of the old Bohemia jeep trail, put tag on jeep trail.

NOTE: (Field notes says cap mkd. 32 and 5, but corner is for 35 and 2)

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23387-8)

The ¼ sec. cor. of secs. 2 & 35, on the S. bdy. of the Tp., perpetuated by the Douglas Co. Surveyor's Office in 1970, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground (alongside of which is the original basalt stone, 12x9x5", mkd. with ¼ on side and X on top, as reset by the DCSO in 1970), with a brass cap mkd.

COUNTY SURVEYORS OFFICE

 T23S R1W

 ¼ S 35

 S 2

 T24S

 1970

continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; S 2, T24-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A fir stump, 29" dia., 4 ft. high, bears N.75°E., 20.5
ft., with a healed blaze.
A fir stump, 31" dia., 6 ft. high, bears S.44°W., 16.5
ft., with a healed blaze.
and new bearing trees
A fir, 23" dia., bears N.25½°E., 87.5 ft., mkd. ¼ S35 BT.
A fir, 15" dia., bears S.63¼°E., 31.0 ft., mkd. ¼ S2 BT.