

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2145)

-----  
Set a basalt stone, 12x10x6 ins., 9 ins., in the ground for ¼ sec. cor., mkd: ¼ on N. face; from which  
A Fir, 36" dia., bears S.75°E., 53 lks., mkd: ¼ S BT.  
A Fir, 6" dia., bears N.10°W., 30 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Harold Corbin, Cadastral Surveyor, under Group # 345 & 350, surveyed April/Oct. 1960 - (DCSO records Vol. 31 Page(s) 12967)

-----  
The ¼ sec. cor. of secs. 26 & 35, monumented with the orig.. basalt stone, 12x10x6 ins., firmly set, 4" above the ground, mkd. ¼ on the N face, from which the remaining OBT:  
A Fir, 55" dia., bears S.65°E., 53 lks., with healed blaze. (Rec. bearing S.75°E.)

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, & set in a mound of stone, 3 ft. base to top, with brass cap marked:  
T23S R1W  
¼  $\frac{S\ 26}{S\ 35}$   
1960

from which  
A Fir, 15" dia., bears N.44½°E., 42 lks., mkd: ¼ S26 BT.  
Deposit orig. corner stone alongside iron post.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23391-2)

-----  
The ¼ sec. cor. of secs. 26 & 35, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, (alongside of which is the original basalt stone, 12x10x6", mkd. /4) with a brass cap (properly) mkd.  
from which the remaining orig. BT reported by Corbin in 1960  
A fir, 53" dia., bears S.70°E., 35.0 ft., with a healed blaze. (Record, S.65°E.)  
and a new bearing tree  
A cedar, 22" dia., bears N.5½°W., 16.7 ft., mkd. ¼ S26 BT.