

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2140)

Set a basalt stone, 12x10x5 ins., 9 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on W. face; from which
A Fir, 13" dia., bears N.50°W., 49 lks., mkd: 1/4 S BT.
A Fir, 9" dia., bears N.28°E., 47 lks., mkd: 1/4 S BT.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Dec. 1977 - M 65-51

Found - Basalt stone & orig.
BT which bears N.48°W., 31.4 ft., fd. scribing "1/4S" was 13" now 25" Fir.
1/4 X on west face of stone.
Set - 2 1/2" x 36" I.P. with brass cap mkd. T23S R1W 1/4 S35 S36 1977 PLS 536. Placed orig. stone alongside of pipe on West side.
6" Fir bears S.56°30'W., 7.2 ft. scribed 1/4 S35 BT.
6" Hemlock bears S.72°30'E., 26.3 ft. scribed 1/4 S36 BT.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2763, surveyed April/July 2015 - (DCSO records Vol. 58 Page(s) 23394-5)

The 1/4 sec. cor. of secs. 35 and 36, perpetuated by Baughman, in 1977, monumented with an iron post, 2 1/2" dia., firmly set, projecting 5" above ground, in a mound of stone, 3 ft. base, to the top, with a brass cap (properly) mkd.

T23S R1W
1/4
S 35|S 36
1977
PLS 536

from which the remaining original bearing tree
A fir, 32" dia., bears N.50°W., 32.3 ft., with scribe marks BT visible on an open blaze.
and the bearing trees mkd. by Baughman
A hemlock, 10" dia., bears S.73 3/4°E., 26.3 ft., with scribe marks 36 visible on a partially healed blaze.
A fir, 13" dia., bears S.55 1/2°W., 7.2 ft., with a healed blaze.
A steel fence post is N., 3 ft., from the cor.