

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description


GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2140-1)

-
- Set basalt stone, 12x10x5 ins. 9" in the ground, marked with 1 notch on S & E edges, for cor. to secs. 25, 26, 35, & 36, from which
- A Hemlock, 5" dia., bears N.20°E., 16 lks., mkd: T23S R1W S25 BT.
 - A Fir, 30" dia., bears S.50°E., 10 lks., mkd: T23S R1W S36 BT.
 - A Cedar, 14" dia., bears S.20°W., 13 lks., mkd: T23S R1W S35 BT.
 - A Fir, 36" dia., bears N.65°W., 39 lks., mkd: T23S R1W S26 BT.

BLM Dependent resurvey by Harold Corbin, Cadastral Surveyor, under Group # 345 & 350, surveyed April/Oct. 1960 - (DCSO records Vol. 31 Page(s) 12962-3)

-
- From the cor. of secs. 25, 26, 35 & 36, monumented with the orig. basalt stone, 12x10x5 ins., firmly set 6 ins. above the ground, marked with 1 notch on the S & E edge, from which the OBTs:
- A Hemlock, 10" dia., bears N.20°E., 16 lks., with a healed blaze.
 - A Fir, 39" dia., bears S.50°E., 10 lks., bark scribed T23S R1W S36 BT.
 - A Cedar, 18" dia., bears S.20°W., 13 lks., with a healed blaze.
 - A Fir, 39" dia., bears N.65°W., 36 lks., with a healed blaze. (Record distance, 39 lks.)

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 2 ft. base to top, w/brass cap mkd:



Deposit orig. corner stone alongside iron post.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - P. Earle - Oct. 21, 1976 - C.S. File 59/24-39

Found - 1960 GLO brass cap dislodged & laying under down BT.
Also found 4 OBTs. The trees in the SE & SW quads are now windfalls.
continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Renewal- I re-stamp date on brass cap "1976" and place at corner point.
Orig. 10" now 12" Hemlock bears N.20°E., 9.3 ft., (rec. 10.6 ft.) Tree has well healed blaze facing away from corner approx. 45°.
Orig. 39" now 42" Fir, bears N.65°W., 23.8 ft. (1960 rec. 23.8, Orig. 25.7 ft.) Tree has well healed blaze.
New BTs- An 8" Hemlock, bears S.6½°W., 28.1 ft., tree blazed & scribed "S35 CS BT"
A 10" Hemlock, bears S.62½°E., 35.5 ft., tree double blazed & scribed "T23S R1W S36 CS BT"
Set - Yew post, squared approx. 2", 5 ft. long, 1 ft. in the ground. Mound of stones around base of post. Post bears East, 3 ft.