

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2141)

Set a basalt stone, 12x8x6 ins., 9 ins., in the ground for ¼ sec. cor., mkd: ¼ on N. face; from which

A Fir, 36" dia., bears S.50°E., 18 lks., mkd: ¼ S BT.

A Fir, 24" dia., bears N.20°W., 24 lks., mkd: ¼ S BT.

DCSO not fd 10/7/1970 C.S. File 54/27-154 - Logged & extensively & burned.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Dec. 1977 - M 65-51

Set - 2½" x 36" I.P. with brass cap mkd. T23S R1W 1/4 S25 S36 1977 PLS 536., from which

12" Hemlock bears S.38°E., 13.2 ft., scribed ¼ S36 BT.

15" Hemlock bears N.54°W., 17.9 ft., scribed ¼ S25 BT.