TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2133)

---

Set basalt stone 12x7x6 ins., 9" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Chinquapin 3" dia., bears N.12°W., 29 lks. dist. mkd. ¼ S BT.
A Chinquapin 3" dia., bears N.20°E., 53 lks. dist. mkd. ¼ S BT.

GLO Resurvey by John G. Collins; Dan P. Mumbrue; Theodore Vander Meer, under Special Instructions, dated May 9, 1922 - (DCSO records Vol. 5 Page(s) 2163)

---

Proportional measurement.
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor. of sec. 36 only, with brass cap mkd. ¼ S36
1925
No trees within limits; raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Dec. 1977 - M 65-51

---

Set 2½" x 36" I.P. with brass cap mkd. T23S R1W R1E 1/4 S36 1977 PLS 536., from which
16" D.Fir bears N.20°E., 17.2 ft. scribed ¼ S36 BT.
18" D.Fir bears S.63°W., 39.0 ft. scribed ¼ S36 BT.