

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 700151

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T23-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John G. Collins; Dan P. Mumbrue; Theodore Vander Meer; under special instructions, dated May 9, 1922 - (DCSO records Vol. 5 Page(s) 2164-65)

-----  
A point 40.00 chains southing from the point for the cor. of secs. 30 and 31 only, determined as hereinafter set forth. Set an Iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor. of sec. 31 only with brass cap mkd.

¼ S 31  
1925

from which

A Fir 12" dia., bears N.50°E., 54 lks. dist. mkd. ¼ S31 BT.

A Fir 6" dia., bears S.26°E., 28 lks. dist. mkd. ¼ S31 BT.

Douglas County Surveyors Office - Vic Cangie & Michael Tompkins - Nov. 2, 1976 - C.S. File 59/26-5

-----  
Found - 1925 GLO brass cap properly marked.  
6" now 15" Fir bears S.26°E., 18.5 ft. We open and find scribing. Tree alive and well.  
12" now 34" Fir bears N.50°E., 39 ft. (Rec. 35.6 ft.) Tree alive and well.

At corner point, We reset iron pipe with brass cap uprooted at site.

New BT - An 8" Fir bears S.63½°E., 17 ft. scribed ¼ S31 CS BT with double blaze.

Corner is 50 ft. West of Road 2422 Z.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 5-1-2025 - C.S. File 67/60-28

-----  
Found - 1925 GLO brass cap.  
Burned dead 26" fir S.26°E. 18.5ft. Rehealed blaze add 3½" mag nail, right side center.  
Burned dead 42" fir N.52°E. 39.0ft (Rec N.50°E.) Fully healed single blaze. Add 3½" mag nail right side center.  
Burned dead 13" fir S.61½°E. 17.0ft (Rec S.63°E.) Fully healed double blaze. Add 3½" mag nail right side center.

2 steel P.N.C. post with U.S.F.S. monument signs. North 1.5ft and East 13.0ft.

New - Burned dead hemlock N.48°E. 13.2ft with 3½" mag nail right side center.

Notes - Mon. is 50'± west of road 2422Z.

Continued next page

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 700151

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T23-1W

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Compass decl. 14½°E.  
OCRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
N. 688003.211 E. 4326865.319