

TOWNSHIP 23 RANGE 01 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2132)

Set basalt stone 12x12x8 ins., 9" in the ground for ¼ sec. cor. mkd. on W. face, from which
A Fir 36" dia., bears S.2°W., 41 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears S.37½°E., 41 lks. dist. mkd. ¼ S BT

GLO resurvey by John Collins; Dan Mumbrue; Theodore Vander Meer, under Special Instructions, dated May 9, 1922 - (DCSO records Vol. 5 Page(s) 2166-67)

The old ¼ sec. cor., which is a basalt stone, 6x10x8 ins., above ground, firmly set, mkd. ¼ on W. face; from which
A Fir snag 30" dia., bears S.40°E., 38 lks. dist. mkd. ¼ S BT.
A Fir snag 50" dia., bears West, 38 lks. dist. mkd. ¼ S BT.
I now change this cor. to refer to sec. 25 only, and mark the stone ¼ S25 on W. face; from which
A Fir 30" dia., bears S.77½°W., 69 lks. dist. mkd. ¼ S25 BT. (New BT)
A Fir 6" dia., bears N.29°W., 47 lks. dist. mkd. ¼ S25 BT. (New BT)