

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32; 5 & 6, T24-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2176)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 5, 6, 31 and 32, mkd. T23S S32 on NE.; R2W S5 on SE.; T24S S6 on SW.; S31 on NW. faces, with 5 notches on E. and 1 notch on W. edges, from which
A Fir 36" dia., bears N.65°E., 30 lks. dist. mkd. T23S R2W S32 BT.
A Fir 24" dia., bears S.55°E., 6 lks. dist. mkd. T24S R2W S5 BT.
A Maple 5" dia., bears N.37°W., 20 lks. dist. mkd. T23S R2W S31 BT.
A Fir 12" dia., bears S.10°W., 26 lks. dist. mkd. T24S R2W S6 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2183-84)

(80.00 chs.)
Set a basalt stone 15x12x5 ins., 10" in the ground for cor. to secs. 5, 6, 31 and 32, mkd. with 5 notches on E. and 1 notch on W. edges, from which
A Fir 24" dia., bears N.27°E., 26 lks. dist. mkd. T23S R2W S32 BT.
A Fir 30" dia., bears S.10°E., 37 lks. dist. mkd. T24S R2W S5 BT.
A Fir 36" dia., bears S.66°W., 31 lks. dist. mkd. T24S R2W S6 BT.
A Fir 36" dia., bears N.15°W., 30 lks. dist. mkd. T23S R2W S31 BT.
West, 0.50 chs.)
Old sec. cor., a post bears South, 3.40 chs. dist. I destroyed this post, also the marks on the old bearing trees.

Weyerhaeuser Co. - 1958-1963 - C.S. File 53/106-7

Found - 15"x12"x5" basalt stone, gone. A deep logging skid road at point for corner.
1953 survey record:
36" Fir N.17°W., 19.9 ft., now stump, plate gone, bark gone. (Orig. bark scribe present)
38" Fir S.77°W., 18.1 ft., now stump, no writing on plate.
32" Fir, East 26.9 ft., now stump, plate gone.
(Cont. Next Page)

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32; 5 & 6, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

30" Fir, now stump, S.45°E., 40.8 ft., no writing on
plate.
Accessories added, 1958:
"W" nails and plates to all four Fir stumps, as
shown above.