

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & 5, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2175)

-----

Set Hemlock post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. corner, marked 1/4 S. on N. face, from which  
A Maple 6" dia., bears N.35°W., 24 lks. dist. mkd. 1/4 S BT  
A Maple 5" dia., bears S.20°E., 24 lks. dist. mkd. 1/4 S BT

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2183)

-----

(39.50 chs.)  
Old 1/4 sec. cor., a post bears S. 4.50 chs. I destroyed this cor. also the marks on the old bearing trees.  
(40.00 chs. West)  
Set a post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 on N. face, from which  
A Vine Maple 5" dia., bears N.47°E., 16 lks. dist. mkd. 1/4 S BT.  
A Fir 30" dia., bears S.60°E., 27 lks. dist. mkd. 1/4 S BT.

Weyerhaeuser Co. - 1958-1963 - C.S. File 53/106-8

-----

Found - 30" Fir S.60°E., 17.82 ft., now 33" Fir stump, chopped out. (Orig. BT)  
No trace of 5" Vine Maple N.47°E., 10.56 ft.  
Set 5/8" x 30" Monel pipe with a 2" x 19.6 ft. black iron pipe, set 17 ft. NE., 3 ft. in ground.  
BTs - 42" Fir stump N.24°E., 28.8 ft. "W" nail & plate.  
33" Fir stump S.60°E., 17.8 ft. "W" nail & plate.  
(orig. BT)