

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2200)

Set a basalt stone, 16x10x6 ins., 12 ins., in the ground for 1/4 sec. cor., mkd: 1/4 on W. face; from which
A Fir, 26" dia., bears S.48°E., 159 lks., mkd: 1/4 S BT.
A Fir, 36" dia., bears S.10°W., 148 lks., mkd: 1/4 S BT.

Weyerhaeuser Co. - John E. Wilson, Log. Eng. - Oct. 1964 - C.S. File 51/306 & C.S. File 53/106-2

Found - GLO record, 1894; Stone 16"x10"x6", gone.
26" Fir, now 30", S.48°E., 159 lks., opened upper face & found scribing.
36" Fir, now down 40" S.10°W., 148 lks., 2 healed faces visible. Ref. by Glen McChesney (plate & "W" nails only) Decl. 20°
Set - 1" alum. pipe & mound of stone.
30" Fir, S.48°E., 104.9 ft.
34" Fir S.2°E., 119.0 ft.