

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2174)

On mountain 2000 ft. high, Set Cedar post, 4 ft. long, 4" sq., 24" in the ground for corner to secs. 3, 4, 33 and 34, mkd. T23S S34 on NE.; R2W S3 on SE.; T24S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges, from which

- A Hemlock 30" dia., bears N.60°E., 24 lks. dist. mkd. T23S R2W S34 BT.
- A Hemlock 5" dia., bears S.55°E., 30 lks. dist. mkd. T24S R2W S3 BT.
- A Hemlock 30" dia., bears S.60°W., 28 lks. dist. mkd. T24S R2W S4 BT.
- A Fir 30" dia., N.70°W., 36 lks. dist. T23S R2W S33 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2181)

(80.00 chs.)
 Set a post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 3, 4, 33 and 34, mkd. T23S S34 on NE.; R2W S3 on SE.; T24S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges, from which

- A Hemlock 18" dia., bears N.11°E., 8 lks. dist. mkd. T23S R2W S34 BT.
- A Fir 36" dia., bears S.25°E., 70 lks. dist. mkd. T24S R2W S3 BT.
- A Hemlock 18" dia., bears S.37°W., 9 lks. dist. mkd. T24S R2W S4 BT.
- A Fir 30" dia., bears N.66°W., 55 lks. dist. mkd. T23S R2W S33 BT.

West, 2.50 chs.)
 Old sec. cor., a post bears South 40 lks. dist., I destroyed this post, also the marks on the old bearing trees.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 1969 - C.S. File 54/27-161

Found - Orig. 36" now 48" Fir, alive, S.25°E., 46.2 ft., open and scribe visible.
 Orig. 18" Hemlock N.11°E., 5.3 ft., down, face up.
 Other orig. BTs gone.

Set Brass cap at cor. mkd: County Surveyors Office

T23S	R2W	¼	S 33	S 34
T24S			S 4	S 3

(Cont. Next Page) 1969

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T24-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 8" Hemlock N.49°E., 14.0 ft. mkd. T23S R2W S34 CSBT
10" Hemlock S.74°W., 45.5 ft. mkd. T24S R2W S4 CSBT
No other trees suitable.
Brass cap lies toward easterly end of root wad of orig. BT to NE.

Douglas County Surveyors Office - Karen Reed; S.J. Flause; V. Woodral, crew - July 10, 1979 - C.S. File 60/34-2

Found - 1969 DCS0 brass cap, properly marked.
36" Fir, now 52", bears S.27°E., 43.0 ft. (Rec. S.25°E., 46.2 ft.) Tree has been chopped out, visible scribing "T2 R2W S3 BT".
Orig., a root hole with down Fir bears N.66°W., 36.3 ft. dist. Tree badly rotted.
Orig., an 18" Hemlock, now down, bears N.11°E., 5.3 ft. dist.
Left cap in place.
New BT - A 21" Hemlock scribed "T24S R2W S4 CS BT" bears S.84°W., 51.5 ft.
Corner located at lower center of large rootwad.

Russell Badgley - For: Weyerhaeuser - 10/2021 - M178-42

Found - A 1½" iron pipe by DCS0 in 1969, firmly set 6" below the surface, at the lower center of a large root wad, with a 2½" brass cap (properly) marked
From which the original BTs -
A 52" D.Fir bears S.25°15'E., 43.1 ft (S.27°E., 43.0')
And BTs by the DCS0 in 1969 -
A 22" Hemlock bears N.56°15'E., 13.7 ft (N.49°E., 14.0')
A 27" Hemlock bears S.74°15'W., 46.2 FT (S.74°W., 45.5')
And BTs by DCS0 in 1979 -
A 36" Hemlock bears S.84°15'W., 50.8 ft (S.84°00'W., 51.5')
New BTs- A 12" Hemlock bears N.56°45'W., 16.1 ft scribed "T23S R2W S33 BT" on double blaze
NAD83 (2011)
LATITUDE 43°31'15.17446"N LONGITUDE 122°55'54.27790"W