

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alis _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2194)

Set basalt stone, 15x10x6 ins. 10" in the ground for ¼ sec. cor. mkd: ¼ on W face, from which
A Cedar, 8" dia., bears S.54°E., 7 lks., mkd: ¼ S BT.
A Fir, 24" dia., bears S.70°W., 20 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1969 - C.S. File 54/27-112

Found - Corner stone mkd: "¼" as called for in orig. notes.
Orig. 8" Cedar, now 14" snag, S.54°E., 4.6 ft. scribe visible on unhealed blaze.
Orig. 24" Fir, now 25" snag, S.70°W., 13.2 ft. scribe visible.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R2W
(Reset stone alongside) OFFICE 1969 ¼ S 27|S 26
New BTs- 18" Hemlock N.76°E., 20.4 ft. mkd: ¼ S26 DCS BT
48" D.Fir N.68°W., 24.4 ft. mkd: ¼ S27 DCS BT
This corner lies on steep NW slope on E-W Lane, Douglas Co. line.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.