

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T24-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2172)

Set Hemlock post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. corner, mkd. 1/4 S. on N. face, from which
A Hemlock 6" dia., bears N.44°E., 11 lks. dist. mkd. 1/4 S BT.
A Hemlock 7" dia., bears S.15°W., 7 lks. dist. mkd. 1/4 S BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2179-80)

(39.00 chs.)
Old 1/4 sec. cor., a post bears South 4.00 chs. I destroyed this post, also the old bearing trees.
(40.00 chs. West)
Set a post 3 ft. long, and 3" sq., 24" in the ground mkd. 1/4 S on N. face, from which
A Fir 30" dia., bears S.68°E., 53 lks. dist. mkd. 1/4 S BT.
A Fir 9" dia., bears N.69°W., 15 lks. dist. mkd. 1/4 S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 1969 - C.S. File 54/27-159

Found - Orig. 1894 30" now 48" Fir, alive, S.68°E., 35.0 ft., shows good scars.
Orig. 1894 9" now 14" Fir, alive, N.69°W., 9.9 ft. open and find scribe.
Set Brass cap at cor. mkd: County Surveyors Office
T23S R2W 1/4 S 35
T24S S 2
1969
New BTs- 20" R.Fir N.18°W., 24.2 ft. mkd. 1/4 S35 CS BT.
10" R.Fir S.52°E., 36.6 ft. mkd. 1/4 S2 CS BT.
Cor. lies on well blazed E-W line approx. 200 ft. W. of old Rock Creek Trail, we put line tag on trail.