

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2193)

Set basalt stone, 12x12x8 ins. 10" in the ground for ¼ sec. cor. mkd: ¼ on N face, from which
A Fir, 36" dia., bears N.42°E., 33 lks., mkd: ¼ S BT.
A Hemlock, 6" dia., bears S.45°E., 21 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1969 - C.S. File 54/27-101

Found - Orig. corner stone, in place & mkd: "¼"
Orig. 36", now 38" Fir, alive, N.42°E., 21.8 ft., shows good scar.
Orig. 6", now 7" Hemlock snag, S.45°E., 13.9 ft., open & shows scribe.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R2W
OFFICE ¼ S 26
1969 S 35

New BTs- 7" Hemlock N.49°E., 23.0 ft., mkd: ¼ S26 CS BT
11" Hemlock S.39°E., 21.1 ft. mkd: ¼ S35 CS BT

This corner lies on westerly slope about 60 ft. W of creek, 4 ft. wide.

Donald L. Peel, LS 752 - For: Triangle Engin. - Aug. 28, 1979 - C.S. 58/176-8

Found - 1969 County brass cap in place, in a mound of stone.
Orig. Fir, 40" bears N.43°E., 21.8 ft. closed face.
Orig. Hemlock snag, down.
2 county BTs, now down.

New BT - A 42" Fir stump, bears S.1°E., 63.3 ft. scribed ¼ S35 BT.