

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T24-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 - (DCSO records Vol. 5 Page(s) 2171-72)

-----  
Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 2, 35 and 36, mkd. T23S S36 on NE.; R2W S1 on SE.; T24S S2 on SW.; and S35 on NW. faces, with one notch on E. and 5 notches on W. edges, from which  
A Fir 30" dia., bears N.30°E., 15 lks. dist. mkd. T23S R2W S36 BT.  
A Fir 50" dia., bears S.61°E., 10 lks. dist. mkd. T24S R2W S1 BT.  
A Sugar Pine 36" dia., bears S.59°W., 45 lks. dist. mkd. T24S R2W S2 BT.  
A Fir 36" dia., bears N.50°W., 7 lks. dist. mkd. T23S R2W S35 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2179)

-----  
(79.75 chs.)  
The old sec. cor., a post bears South, 100 lks. I destroyed this post, also the marks on old bearing trees.  
(80.00 chs. West)  
Set a post 4 ft. long and 4" sq., 24" in the ground for cor. to secs. 1, 2, 35 and 36, mkd. T23S S36 on NE.; R2W S1 on SE.; T24S S2 on SW.; and S35 on NW.; faces with 1 notch on E. and 5 notches on W. edges, from which  
A Fir 18" dia., bears N.53°E., 21 lks. dist. mkd. T23S R2W S36 BT.  
A Fir 30" dia., bears S.49°E., 57 lks. dist. mkd. T24S R2W S1 BT.  
A Fir 48" dia., bears S.25°W., 32 lks. dist. mkd. T24S R2W S2 BT.  
A Fir 30" dia., bears N.28°W., 29 lks. dist. mkd. T23S R2W S35 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 1969 - C.S. File 54/27-158

-----  
Found - Orig. 18" now 20" Fir snag, N.53°E., 13.9 ft., open, scribe visible.  
Orig. 30" now 40" Fir, alive, S.29°E., 37.6 ft. (Rec. S.49°E.), shows good scar.  
Orig. 48" now 58" Fir, alive, S.25°W., 21.1 ft., shows good scar.

(Cont. Next Page)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Orig. 30" now 38" Fir, alive, N.28°W., 19.1 ft., shows good scar.  
Set Brass cap at cor. mkd: County Surveyors Office  
T23S R2W S 35 | S 36  
T24S S 2 | S 1  
1969  
New BT - 52" D.Fir N.13°E., 74.4 ft. mkd. "T23S R2W S36 CS BT"  
No smaller trees available. This corner lies on moderate SW. slope in old growth timber.

---

Douglas County Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart, crew - Sept. 8, 1981 - C.S. File 61/27-37  
-----  
Found - Brass cap, firmly set, protruding 11" out of ground, properly marked.  
20" decayed stump, (Orig. 18" Fir), and log bears N.53°E., 13.9 ft., no face or scribing visible.  
33" stump, (orig. 30" Fir), with bark removed and metal cover on top, bears S.29°E., 37.6 ft. (Rec. S.49°E.), no scar visible, with bark off.  
65" stump (orig. 48" Fir), bears S.25°W., 21.1 ft. Stump is cut low. No face or scribing visible.  
38" blowdown (orig. 30" Fir), with well healed double blaze, bears N.28°W., 19.1 ft. to center of root hole.  
60" stump (orig. 52" Fir) with scribed "S BT" visible, bears N.13°E., 74.4 ft.

New Accessories:  
Set PK nail in burl on 45" Fir stump (stump has bark off and metal cover on top) which bears S.81°E., 20.0 ft.  
"W" nail 1.0 ft. above ground in 80" Fir stump, bears N.62°E., 31.5 ft.  
"W" nail near ground of orig. 30" now 33" Fir stump, bears S.29°E., 35.6 ft.  
44" Fir bears N.85°W., 12.9 ft. scribed "T23S R2W S35 CS BT" in single blaze. Old axe marks above new blaze.

---

2