

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2188-9)

Set a post 4 ft. long 4" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ on W face from which
A Fir, 8" dia., bears East, 29 lks., mkd: ¼ S BT.
A Fir, 12" dia., bears N.65°W., 33 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1969 - C.S. File 54/27-103

Found - Stone 15"x18"x12" mkd: "X" on top, not called for in notes.
Orig. 8" now 18" Fir, down, East 19.1 ft. open to old blaze, not scribed.
Orig. 12" now 22" Fir, down, N.65°E., 21.8 ft., open & find scribe.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R2W (reset stone alongside) OFFICE 1969 ¼ S35| S36
6" Fir N.46°W., 14.9 ft., mkd: ¼ S35 CS BT.
11" Fir N.79°E., 31.0 ft. mkd: ¼ S36 CS BT
This corner lies 15 ft. north of small creek, course east.