

TOWNSHIP 23 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2190)

-----  
Set basalt stone, 14x8x6 ins. 9" in the ground for ¼ sec. cor. mkd: ¼ on N face, from which  
A Fir, 36" dia., bears N.74°E., 47 lks., mkd: ¼ S BT.  
A Cedar, 12" dia., bears S.60°E., 19 lks., mkd: ¼ S BT.

Georgia Pacific Timber Co. - Sept. 1962, added 1/5/2012 - C.S. File 65/76-3

-----  
Found - Stone 14"x8"x6" ¼ N face.  
24" cedar 12.5 S.60°E., ¼ S BT.  
42" fir 31.0 N.74°E., mk. ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1969 - C.S. File 54/27-108

-----  
Found - No trace of corner stone called for.  
Orig. 36" now 40" Fir snag, N.74°E., 31.0 ft. open & find scribe.  
Orig. 12" now 24" Cedar, alive, S.60°E., 12.5 ft., shows good scars. Rescribe: ¼ S36 CS BT  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R2W  
OFFICE ¼ S 25  
1969 S 36  
18" Hemlock N.59°E., 38.1 ft., mkd: ¼ S25 CS BT  
This corner lies at bottom of nearly vertical rock bluff 50' high NE.