

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T23-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 5 Page(s) 2127)

-----  
Set a Cedar post 4 ft. long, 24" in the ground 4" sq., for corner to secs. 25, 30, 31 and 36, marked T23S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 5 notches on N. and 1 notch on S. edges, from which  
A Fir 20" dia., bears S.45°E., 52 lks. dist. mkd. T23S R1W S31 BT.  
A Fir 6" dia., bears N.32°E., 26 lks. dist. mkd. T23S R1W S30 BT.  
A Fir 20" dia., bears S.38°W., 7 lks. dist. mkd. T23S R2W S36 BT.  
A Fir 24" dia., bears N.57°W., 31 lks. dist. mkd. T23S R2W S25 BT.

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2130)

-----  
(73.40 chs.)  
The old sec. cor. which I destroy.  
(80.00 chs.)  
Set a post 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 25, 30, 31 and 36 mkd. T23S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 1 notch on S. and 5 notches on N. edges, from which  
A Cedar 20" dia., bears N.16°E., 36 lks. dist. mkd. T23S R1W S30 BT.  
A Fir 30" dia., bears S.56°E., 17 lks. dist. mkd. T23S R1W S31 BT.  
A Cedar 20" dia., bears S.72°W., 58 lks. dist. mkd. T23S R2W S36 BT.  
A Fir 20" dia., bears N.65°W., 37 lks. dist. mkd. T23S R2W S25 BT.

Georgia Pacific Timber Co. - Sept. 1962, added 1/5/2012 - C.S. File 65/76-3

-----  
Found - 1½ Iron pipe  
32" fir N.40°W., 27.7 GP tag CS BT  
28" hem N.55°E., 36.2 GP tag CS BT  
60" fir S.65°W., 28.8 GP tag CS BT.  
40" fir S.56°E., 11.2 BLM tag CS BT

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T23-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Wm.W. Glenn and Harvey E. Wofford, Cadastral Surveyors, under Group #345, Surveyed Sept. 1964/July 1966 - (DCSO records Vol. 35 Page(s) 14306)

-----  
The Sec. Cor., monumented with an iron pipe, 48" long, 2" dia., firmly set, protruding 24" above ground, from which the remaining original bearing trees:

A burned Cedar stump 32" dia., bears N.16°E., 36 lks. dist. no marks visible.

A Fir 40" dia., bears S.56°E., 17 lks. dist. with scribe marks T23S R1W S31 BT visible on bark blaze.

A burned Cedar snag 30" dia., bears S.72°W., 58 lks. dist., with open and burned blaze.

and locally established bearing trees

Fir 60" dia., bears S.62¼°W., 46 lks. dist., with scribe marks CS BT visible on open blaze.

A Hemlock stump 30" dia., bears S.45½°E., 57 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

	T	23	S
R	2	W	R 1 W
	S	25	S 30
	S	36	S 31
			1964

from which

A Fir stump 35" dia., bears N.56°E., 74 lks. dist. mkd. T23S R1W S30 BT.

A Fir stump 36" dia., bears N.43½°W., 44 lks. dist. mkd. T23S R2W S25 BT.

Reset iron pipe alongside the iron post.

The corner is located at the N. edge of heavy timber on a steep NW. slope, bears E. and W.

Fd. OK, March 1973 by Nick Juliano - C.S. File 58/24

David Wellman - For: Weyerhaeuser Co. - 7/8/2004 - C.S. File 65/52-1 A&B

-----  
Found - 32" Cedar stump, 1964 BLM tag reads "S.16°W., 36 lks." OBT

40" Fir stump, 1986 BLM tag reads "N.56°W., 17 lks." tin cap - OBT

35" Fir stump, 1964 BLM tag reads "S.56°W., 74 lks." scribing visible.

36" Fir stump, 1964 BLM tag reads "S.43½°E., 44 lks." scribing visible.

continued next page

