

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 100104

PRIMARY CORNER DESCRIPTION C C Sec. 36, T23-4; and S. 1, T24-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 6 Page(s) 2320-21)

At a point of intersection, 4.71 chs. N. of SW. Cor. T23S R3W, Set a Hemlock post 3 ft. long, 4" sq., 24" in the ground, for closing corner of T23 and 24 S., R4W, marked CC R4W on W.; T23S S36 on N.; and T24S S1 on S. faces with 6 grooves on the N.; S. and W. faces, from which

A Hemlock 16" dia., bears N.16°W., 9 lks. dist. mkd. T23S R4W S36 BT.

A Hemlock 20" dia., bears S.40°W., 52 lks. dist. mkd. T24S R4W S1 BT.

This cor. is on a hillside, sloping E.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11458)

The closing corner (on the verge of obliteration) is determined from the remains of the original bearing trees;

A stumphole bears N.16°W., 9 lks. dist.

A stumphole bears S.40°W., 52 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 3" dia., 28" in the ground, with brass cap mkd:

	T 23 S	T 23 S
	R 4 W	
CC	S 36	S 31
	S 1	
	T 24 S	R 3 W
	1950	

from which

A Cedar 9" dia., bears N.32°45'W., 101 lks. dist. mkd. T23S R4W S36 CC BT.

A Fir 36" dia., bears S.77¼°W., 182 lks. dist. mkd. T24S R4W S1 CC BT.

Glen McChesney - Weyerhaeuser Co. - June 6, 1961 - C.S. File 53/108

Found - 1950 brass cap in mound of stone.

9" now 12" Cedar, scribing visible, N.30°W., 64.8 ft., dist. to face.

36" now 40" Fir, stump, scribing visible, S.79°W., 118.3 ft., dist. to face.

Accessories added this date:

(Cont. Next Page)

