

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 19; & 24, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 6 Page(s) 2296)

-----  
Set a post 4 ft. long, 4" sq., 24" wide in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Fir 36" dia., bears N.10°E., 25 lks. dist. mkd. ¼ S BT  
A Fir 35" dia., bears S.64°W., 20 lks. dist. mkd. ¼ S BT

Wilford Haines - Survey date unknown, filed Dec. 1965 - C.S. File 54/16-23N (added 3/12/2018)

-----  
Found - 40" Fir N.64°W., 13.2 ft. (scribed upside down)  
50" stump, N.24°E., 32 ft. (no scribe)

WEYCO - 2/1957 (ADDED 11/27/2019) - C.S. File 63/48-2 (A&B)

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey - April 1959 (added 7/19/2021) - C.S. File 49/42-8

-----  
I find new scribed stake form which a 24" Fir bears N.63°W., 13.2' barked scribed "¼ S BT" this BT is not an original also it does not agree with unrecorded notes of Thiel.  
I believe the 24" fir was bark scribed by Thiel also it seems to be quiet old.

Survey by Donald Branch, LS #1137 - For: U.S. Bank - C.S. 63/48 and M 104-1

-----  
No monument found.  
Found - A 54" Fir stump with sign that says corner bears S.28°W., 32.4 ft.  
42" Fir in NW. quadrant gone.  
Set spike nail with L.S. cap in log for ¼ corner (S.28°W., 32.4 ft. from 54" BT.)  
New BTs- 3" D.Fir bears S.70°W., 2.7 ft. with "X" scribed and L.S. Washer.  
2" D.Fir bears S.43°E., 4.1 ft. with "X" scribed and L.S. Washer.