

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.

GL0 survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 6 Page(s) 2295)

A Fir 50" dia., which I mark $\frac{1}{4}$ on W. face for $\frac{1}{4}$ sec. cor., from which

A Yew 8" dia., bears S.40°W., 25 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 40" dia., bears N.10°E., 30 lks. dist. mkd. $\frac{1}{4}$ S BT.

Glen McChesney - Weyerhaeuser Co. - (from Lane Co. Records) -C.S. File 53/1-21 & C.S. File 53/107-21

Found - GL0 survey record, 1882:
50" Fir scribed W. face, found bark scribed " $\frac{1}{4}$ " W. face of 60" Fir.
8" Yew S.40°W., 25 lks., 16.5 ft., now 10" Yew, broken 4 ft. high, dead, scribing visible.
40" Fir N.10°E., 19.8 ft., now 46" Fir, axe marks not chopped, possibly was bark scribed and flaked off.

Set 5/16 Iron rod in West root-swell of 60" corner Fir. Base of rod is 6" West of bark scribing.
S.18 $\frac{1}{2}$ °W., 23.0 ft. dist. & brg. taken to scribing on W. face corner Fir to scribed Yew.
N.6°W., 19.8 ft. from scribing on W. face corner Fir to 46" Fir. (GL0 brg. probably should be N.10°W., instead of N.10°E.)

New BTs- 56" Fir N.22°E., 35.0 ft.
48" Fir S.46°W., 31.0 ft.

Les Roberts - For: John Moffitt - Nov. 21, 1997 - M 127-75

Found - 60' up-rooted Fir stump (no marks). Stump has 5/16" iron rod in root swell.
48" Fir stump, S.46°W., 31' (scar vis.), Wey Co BT
56" Fir stump, N.22°E., 35' (scar vis.), Wey Co BT
New - Wooden hub in center of 60" Fir root hole for east 1/4 corner.

continued next page

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T23-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2147, surveyed Aug/Nov. 2006 - (DCSO rec. Vol. 55 Page(s) 21405-6)

The ¼ sec. cor. of secs. 13 and 18, perpetuated by McChesney, in 1958, determined at record dist. from the original NE. bearing tree and record bearing from McChesney's SW. bearing tree, reported by the Douglas County Surveyor's Office, in 1997, alongside of which is the uprooted original fir corner tree, 56" dia., with fragmentary scribing visible, from which the remains of an original bearing tree

A sawed fir stump, 45" dia., bears N.6½°E., 19.8 ft., with no marks visible. (Record, N.10°E.)

and the remains of bearing trees mkd. by McChesney

A sawed fir stump, 58" dia., bears N.23°E., 38.6 ft., with no marks visible, and a W nail in the face.

A sawed fir stump, 48" dia., bears S.46°W., 30.9 ft., with a healed blaze, and a W nail in the healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½" dia., 24 ins. in the ground, with brass cap mkd.

T 23 S

¼

R 4 W R 3 W

S 13 | S 18

2006

from which new bearing trees

A fir, 8" dia., bears N.11½°E., 30.5 ft., mkd. ¼ S18 BT.

A fir, 8" dia., bears N.84°W., 21.2 ft., mkd. ¼ S13 BT.

Each new bearing tree has a 2½" x ¼" magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (CORS 96)) of the following corner was determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations "DCSO CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows: The ¼ section corner of sections 13 and 18 on the east boundary of the township.

Latitude: 43°34'10.49"N. Longitude: 123°06'26.41"W.

Deposit a magnet in a white plastic case at the base of the stainless steel post.