

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T24-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2211-12)

 Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 5, 6, 31 and 32, marked with 5 notches on E. and 1 notch on W. faces, from which
 A Dogwood 7" dia., bears N.35°E., 3 lks. dist. mkd. T23S R3W S32 BT.
 A Dogwood 6" dia., bears N.55°W., 50 lks. dist. mkd. T23S R3W S31 BT.
 A Yew 12" dia., bears S.55°W., 10 lks. mkd. T24S R3W S6 BT
 A Fir 30" dia., bears S.20°E., 3 lks. mkd. T24S R3W S5 BT.

BLM Resurvey by Norman D. Price, Cadastral Surveyor, Under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11459)

 The Sec. Cor. monumented with a Yew 11" dia., (Rec. a post 4 ft. long, 4" sq.) with decayed blazes on NE.; SE.; SW.; and NW. sides on which illegible scribe marks remain; from which the surviving original bearing trees:

A Fir 42" dia., bears S.22°E., 34 lks. dist. with partial scribe marks on old bark blaze. (Rec. S.20°E., 3 lks. dist.)
 A Yew 14" dia., bears S.60°W., 10 lks. dist., with the scribe marks S6 T BT visible on decayed old blaze. (Rec. brg. S.55°W.)

Under center of corner tree, which is badly decayed on E side: Set an iron post 3 ft. long, 2' dia., 34" in the ground with brass cap mkd.

T 23 S R 3 W
S 31 S 32
S 6 S 5
T 24 S
1950

from which

A Yew 18" dia. bears N.38½°E., 49 lks mkd. T23S R3W S32 BT
 A Yew 7" dia. bears N.49°45'W. 42 lks mkd. T23S R3W S31 BT

Marion D. Hale - For: Weyerhaeuser Co. - Nov. 1961 - C.S. File 51/31-2

 Found - 1950 resurvey brass cap.
 18" Yew N.38½°E., 49 lks.; now dead, scribing visible. (1950)
 42" Fir S.22°E., 34 lks.; faint scribing visible.
 14" Yew S.60°W., 10 lks.; pushed over slightly.

continued next page

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T24-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

7" Yew N.49 3/4°W., 42 lks.; shattered off close to ground by logging.
Referenced by M. Hale (plates & "W" nails only) Nov. 1958 (C.S. 53/111-6):
46" Fir stump N.13°E., 52.7 ft.
42" Fir S.19°E., 22.6 ft.
50" Fir S.70°W., 53.8 ft.
44" Fir stump N.26°W., 46.1 ft.

Survey by Donald Peel - For: Weyerhaeuser and Champion International - Oct. 1979 - M 80-57

Found - 2" Iron pipe with 1950 GLO brass cap.
18" Yew snag, N.41°E., 31.9 ft.
60" Fir stump, S.70°W., 53.8 ft. (brg. & dist. to "W" nail.)
New BT - 8" Fir bears N.53°E., 15.4 ft.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2500 Admin file No. 1408, surveyed July/Aug. 2014 - (DCSO records Plat T24-3-2016-1 all info on plat & Vol. 58 Page(s) 23321-2

The cor. of secs. 5, 6, 31, & 32, on the N. bdy. of the Tp., perpetuated by Hale, in 1958, and Peel, in 1979, monumented with an iron post, 2" dia, firmly set, projecting 4" above the ground, with a brass cap (properly) mkd. from which the remains of a BT mkd. by Price in 1950
A yew stump, 18" dia, bears N.38½°E., 32.3 ft., with no marks visible.
and remains of bearing trees mkd. by Hale
A decayed fir stump, 60" dia. bears N.11¼°E., 55.6 ft., with no marks visible.
A decayed fir stump, 54" dia. bears S.69°W., 56.3 ft., with no marks visible.
A fir stump, 49" dia. N.26½°W., 47.2 ft with no marks visible.
and remains of a BT by Peel
A fir stump, 20" dia. bears N.51¾°E., 15.9 ft. with a healed blaze.
and bearing trees mkd. by person(s) unknown
A fir, 14" dia, bears S.29½°E., 16.7 ft., with no marks visible, and a Weyerhaeuser tag.
A fir, 14" dia, bears S.21½°W., 14.2 ft., with no marks visible and a Weyerhaeuser tag.

continued next page

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T24-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new accessories
An iron rod, 30" long, 5/8" dia., driven 25" in the ground for a reference monument, bears N.33°27'09"E., 14.75 ft., with brass cap mkd. RM T23S R3W S32 14.7 FT TO COR 2014, and an arrow pointing to the cor.
An iron rod, 30" long, 5/8" dia., driven 29" in the ground for a reference monument, bears N.50°35'32"W., 15.13 ft., with brass cap mkd. RM T23S R3W S31 15.1 FT TO COR 2014, and an arrow pointing to the cor.