

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2252)

Set a post 4 ft. long 4" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ on W face from which

 A Fir, 50" dia., bears East, 10 lks., mkd: ¼ S BT.

 A Fir, 36" dia., bears S.10°W., 43 lks., mkd: ¼ S BT.

Gilbert A. Gardner - June 2, 1954 - C.S. File 53/1-18

Rescribed orig. 15" D.Fir 6.6 ft. East of corner.
50" D.Fir bears S.28°W., 18.0 ft.

Weyerhaeuser - Robert Barta - 7/29/1959 (added 11/10/2020) - C.S. File 53/107-8

Fd. 2 orig. BTs with "W" nail and Plate

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - Nov. 1967 - C.S. File 54/16-52A (added 3/13/2018)

Reported as fd
½" IP & probably orig. BT stumps - see 1954 report.