

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2255)

A post 4 ft long 4" sq. 24" in the ground for ¼ sec. cor. marked ¼ S on W face from which
 A hemlock, 36" dia., bears South, 25 lks., mkd: ¼ S BT.
 A yew, 7" dia., bears N.30°E., 20 lks., mkd: ¼ S BT.

Gilbert A. Gardner - June 2, 1954 - C.S. File 53/1

39.0 ft N.75°E. from yellow tag on bearing stump to 38" D.Fir stump.
48" Cedar stump bears S.88°W., 53.0 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - Nov. 1967 - C.S. File 54/16-52A (added 3/13/2018)

Reported as not fd
We find 3 stumps that fit for bearing, but distances are off 10 ft to fir stump & 4.0 ft. short to SW Cedar stump. No scribe burned & decayed - dense brush & reprod.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.