

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2253)

A Fir, 24" dia., which I mark $\frac{1}{4}$ S on N face for $\frac{1}{4}$ sec. cor. from which

A Dogwood, 8" dia., bears S.5°E., 15 lks., mkd: $\frac{1}{4}$ S BT.

A Dogwood, 7" dia., bears N.14°W., 27 lks., mkd: $\frac{1}{4}$ S BT.

Gilbert A. Gardner - June 2, 1954 - C.S. File 53/1

Stump of tree marked for corner has yellow tags set by J.F. Woodard. Remark stump: $\frac{1}{4}$ BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Oct. 1967 - C.S. File 54/16-25A

? Found ? - Reported as not found.

Find 34" Fir stump & for approx. tag mkd. "Approx. $\frac{1}{4}$ cor" No evidence of orig. BTs - no scar on stump called cor. tree. - " $\frac{1}{4}$ " cut on NE face with axe. Stump burned - no other BTs fd.