

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33; 4 & 5, T24-3

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2212)

 Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 32 and 33 marked 23S R3W on NE.; 24S R3W on SE.; 24S R3W on SW.; and 23S R3W on NW.; with 4 notches on E. and 2 notches on W. faces, from which
 A Maple 6" dia., bears N.40°E., 20 lks. dist. mkd. T23S R3W S33 BT.
 A Maple 5" dia., bears S.60°E., 36 lks. dist. kd. T24S R3W S4 BT.
 A Spruce 36" dia., bears S.5°W., 8 lks. dist. mkd. T24S R3W S3 BT.
 A Maple 7" dia., bears N.25°W., 35 lks. dist. mkd. T23S R3W S32 BT.

BLM resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11460-61)

 The Sec. Cor. as determined from the surviving original bearing trees:
 A Vine Maple 5" dia., bears S.60°E., 36 lks. dist., with surface scar indicating old blaze.
 A Fir 54" dia., bears S.5°W., 8 lks. dist. with partial scribe marks on old bark blaze.
 At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:
 T 23 S R 3 W
 S 32 | S 33
 S 5 | S 4
 T 24 S
 1950

from which
 A Hemlock 8" dia., bears N.53¼°E., 30 lks. dist. mkd. T23S R3W S33 BT.
 A Hemlock 8" dia., bears S.18¼°E., 31 lks. dist. mkd. T24S R3W S4 BT.
 A Hemlock 12" dia., bears S.70°45'W., 56 lks. dist. mkd. T24S R3W S5 BT.
 A Yew 18" dia., bears N.49½°W., 97 lks. dist. mkd. T23S R3W S32 BT.

Glen McChesney - For: Weyerhaeuser Co. - May 16, 1958 - C.S. File 53/111-28

 (Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Found - 1882 post, gone.
Orig. 6" Maple, N.40°E., no trace.
1882, 5" Maple, S.60°E., 36 lks., (23.8 ft.), stub of vine maple.
1882, 36" Spruce, S.5°W., 8 lks. (5.3 ft.), 64" Fir, not a Spruce.
1882, 7" Maple, N.25°W. 35 lks. (23.1 ft.), no trace
1950 brass cap found.
1950, 8" Hemlock now 10", N.53¼°E., 30 lks. (19.8 ft., scribing visible.
1950, 8" Hemlock now 8", S.18¼°E., 31 lks., 20.5 ft., scribing visible.
1950, 12" Hemlock not 14", S.70 3/4°W., 57 lks. (37.5 ft.), scribing visible.
1950, 18" Yew, N.49½°W., 97 lks. (64.0 ft.), scribing visible.

Accessories added this date:

- 8" Hemlock N.52°E., 17.9 ft. with "W" nails and plate.
- 64" Fir S.15°W., 5.0 ft. with "W" nails and plate.
- 8" Hemlock S.16°E., 20.2 ft. with "W" nails and plate.
- 18" Yew N.49°W., 66.0 ft. with "W" nails and plate.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept. 25, 1967 - C.S. File 54/16-53

Found - 1950 GLO brass cap, firmly set and properly mkd.
Orig. Fir to SW., no stump, no bark scribe.
No trace orig. BT to SE.
8" now 16" Hemlock, alive, N.53¼°E., 19.8 ft., scribe marks visible on unhealed blaze.
8" now 14" Hemlock S.18¼°E., 20.5 ft., alive, healed blaze.
12" Hemlock, now stump, S.70°45'E., 37.0 ft., scribe marks visible.
18" Yew now stump, N.49½°W., 64.0 ft., scribe marks visible.
New BTs- 8" Hemlock S.38°W., 18.4 ft. mkd. T23S R3W S5 CS BT
9" Chinquapin N.34°W 12.8 ft. mkd T23S R3W S32 CS BT
Corner lies 150 ft. N. of small creek, dry in cut off area.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, & Robert Browning, Survey Technician, under Group #11739, surveyed July/Oct. 1994 - (DCSO records Vol. 52 Page(s) 20061-2)

The cor. of secs. 4, 5, 32, & 33, monumented with an iron post, 2" dia., firmly set, projecting 16" above ground, with brass cap mkd. continued next page

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T23S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R3W</td> </tr> <tr> <td style="padding: 0 10px;">S32</td> <td style="border-left: 1px solid black; padding: 0 10px;">S33</td> </tr> <tr> <td style="padding: 0 10px;">S5</td> <td style="border-left: 1px solid black; padding: 0 10px;">S4</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">T24S</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1950</td> </tr> </table>	T23S	R3W	S32	S33	S5	S4	T24S		1950	
T23S	R3W									
S32	S33									
S5	S4									
T24S										
1950										
<p>from which the remains of an original bearing tree A sawed fir stump, 55" dia., bears S.5°W., 8 lks., with no marks visible. and the remains of bearing trees mkd. by Price A hemlock, 28" dia., bears N.53¼°E., 27½ lks., with healed blaze. (Record, 30 lks.) A hemlock, 20" dia., bears S.18¼°E., 31 lks., with healed blaze. A sawed yew stump, 19" dia., bears N.49½°W., 97 lks., with scribe marks T23S R3W S32 B visible on partially healed blaze. and the remains of bearing trees mkd. by Tracy, in 1967, A hemlock, 19" dia., bears S.37½°W., 28 lks., with heal blaze. A maple snag, 9" dia., bears N.33½°W., 18 lks., with scribe marks T23S R3W S32 CS BT visible on open double blaze. and a new bearing tree A hemlock, 7" dia., bears N.51¼°W., 18 lks., mkd. T23S R3W S32 BT.</p>										
<p>Dan Baker - For: Weyerhaeuser Co. - 12/2005 - M149-70 ----- Found - 2" iron pipe with USGLO 2½" brass cap "1950" 31" Hemlock, N.60°E., 18.5' - center measure 21" Hemlock, S.16°E., 21.0' - center measure 54" Fir stump, S.15°W., 5.5' - to "W" nail in face. 9" Hemlock, N.51°W., 12.1' - center measure 8"x15' Hemlock snag, N.34°W., 12.8' - center measure Set - 6' fence post alongside.</p>										