

PRIMARY CORNER DESCRIPTION Sec Cor for 33 & 34; 3 & 4, T24-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2213)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 3, 4, 33 and 34 marked T23S R3W S34 on NE.; T24S R3W S3 on SE.; T24S R3W S4 on SW.; and T23S R3W S33 on NW. faces with 3 notches on E. and W. faces, from which
A Spruce 36" dia., bears S.70°E., 35 lks. dist. mkd. T24S R3W S3 BT.
A Spruce 36" dia., bears S.20°W., 11 lks. dist. mkd. T24S R3W S4 BT.
A Fir 36" dia., bears N.60°W., 5 lks. dist. mkd. T23S R3W S33 BT.
A Fir 40" dia., bears N.10°E., 70 lks. dist. mkd. T23S R3W S34 BT.

Weyerhaeuser Co. - 1964 - C.S. File 53/107-12 & C.S. 53/111-5

Found - No evidence of 1882 post.
No evidence, 36" Spruce S.70°E., 23.1 ft. (probably D.Fir)
36" Spruce, 36" D.Fir snag, root wad, corner pt of face.
36" D.Fir now 40" windfall, scribing on bark visible, N.60°W., 3.3 ft.
40" D.Fir now 46" snag, bark sloughed away, no scribing, N.10°E., 46.2 ft.
New BTs- 46" Fir, orig. BT, N.12°E., 17.7 ft. "W" nail and plate.
62" Fir N.58°W., 33.9 ft. "W" nail and plate.
36" Fir S.39°W., 67.8 ft. "W" nail and plate.
36" Fir, (1946 plate), S.17°W., 7.3 ft. (orig. BT), "W" nail and plate.

Dan Baker - For: Weyerhaeuser Co. - 12/2005 - M149-70

Found - 2" monel pipe
46" Fir stump, N.12°E., 17.7' - original
62" Fir stump, N.58°W., 33.9' - to face.
36" Fir stump, S.17°W., 7.3' - original
36" Fir stump, S.39°W., 67.8' - to face.
Set - 19" Fir, N.76°E., 27.3' - scribed "T23S R3W S34 BT"
18" Fir, N.36°W., 16.7' - scribed "T23S R3W S33 BT"
6' fence post alongside.