

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2237)

Set a post 4 ft. long 4" sq. 24" in the ground for cor. to secs. 27, 28, 33, & 34 mkd. T23S S27 on NE, R3W S34 on SE, S33 on SW, and S28 on NW, faces with 1 notch on S and 3 notches on E. edges from which

- A Fir, 48" dia., bears N.60°E., 60 lks., mkd: T23S R3W S27 BT.
- A Maple, 6" dia., bears S.25°E., 45 lks., mkd: T23S R3W S34 BT.
- A Fir, 8" dia., bears S.45°W., 18 lks., mkd: T23S R3W S33 BT.
- A Fir, 36" dia., bears N.14°W., 62 lks., mkd: T23S R3W S28 BT.

Gilbert A Gardner - Witness: Robert Barta - Dec. 28, 1953 - C.S. File 41/239

Set - 2" iron pipe x 48" iron pipe 2" above ground for cor. N.0°36'E., 2596.2 ft. from the ¼ cor. between secs. 33 & 34 T23S R3W, and also S.89°25'W., 2650.9 ft. from the ¼ cor. between secs. 27 & 34, said T & R. Mkd. BTs:

- 6" D.Fir N.43½°E., 31.0 ft., mkd: S 27 R S BT
- 6" Hemlock bears N.48°W., 8.0 ft., mkd: S 28 R S BT.
- 46" D.Fir which has old markings "BT" bears S.39°E., 16.0 ft., remarked S 34 R S BT.
- 6" D.Fir bears S.45½°W., 27.5 ft., mkd: S 33 R S BT.

This location has been used as a NW cor. of sec. 34 for a number of years and shows surveyor and cruiser marks, and although the BT mkd. in the 46" D.Fir does face the right direction, the distances and bearings to this location are approximately the same as those given in the orig. field notes. No evidence of other BTs was found was found, and it is believed that this is the best location possible with available evidence for this corner.

Marion D. Hale - Wit: H.E. Case & W.W. Dixon - For: Weyerhaeuser Timber Co. - Filed June 19, 1959 - C.S. File 51/25 & C.S. File 53/107-6

GLO survey record - all evidence lost.
 Found - 1½" IP, scribed Yew post & witness trees which are the accessories of G.A. Gardner survey filed in the Surveyor's office.
 continued next page

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

50" Fir stump S.38°E., 16.0 ft., partial scribing on bark.
7" Fir N.43°E., 31.0 ft., scribed S27 RS BT.
7" Hemlock N.47°W., 8.1 ft., scribed S28 RS BT.
8" Fir S.47°W., 27.0 ft., scribed S33 RS BT.
Referenced by Marion Hale (plates & "W" nails only) Decl. 20°
50" Fir stump S.38°E., 16.0 ft.
8" Fir S.47°W., 27.0 ft.
5" Fir N.63°W., 7.3 ft.
9" Hemlock N.56°E., 46.1 ft.

Fd OK by Douglas Co. Surveyors Office - Vernon "Ray" Tracy -
Oct. 1967 C.S. File 54/16-25A