

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias	Description

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2238)

A Hemlock, 5" dia., which I mark ¼ S on W side for ¼ sec. cor. from which

- A Hemlock, 5" dia., bears East, 18 lks., mkd: ¼ S BT.
- A Hemlock, 6" dia., bears West, 30 lks., mkd: ¼ S BT.

Marion D. Hale - Wit: H.E. Case & W.W. Dixon - For: Weyerhaeuser Timber Co. - Filed June 19, 1959 - C.S. File 51/25, C.S. 53/1-29 & C.S. File 53/107-4

GLO survey record - All evidence lost.

Set - ½"x36" gal. iron pipe for corner by single proportionate method.

- Referenced by M. Hale (plates & nails only) Decl. 20°: 30" Hemlock stump S.16°W., 53.3 ft.
- 36" Cedar stump S.9°E., 132.0 ft.

Fd OK by DCSO - Vernon "Ray" Tracy - Oct. 1967

Dave Wellman - For: Weyerhaeuser Co. - Erin Heatherstone & Micah Johnstone - June 2003 - C.S. File 65/45-33 A&B

Found - ½" iron pipe - 1.0 feet AGL
1959 SW Hemlock stump BT decayed.
36" Cedar stump, WEYCO tag reads "N.9°W., 132.0 ft. to "W" nail in face.

Set - 1¾"x36" iron pipe w/brass cap dated 2003 - 0.7' AGL
Brass cap set over the top of ½" iron pipe.

- 14" Fir, N.84½°E., 21.9 ft. to spike set side center - scribed "¼ S27 BT"
- 16" Fir, S.78°W., 4.9 ft. to spike set side center - scribed "¼ S28 BT"
- 17" Fir, N.17°E., 15.1 ft. to spike set side center - scribed "¼ S27 BT"

All BTs- W nail driven into a notch low on a tree or stump. BT tag and painted band above the tag.

Note - East, 60 ft. small creek flowing N.20°E.
Corner is approx. 200 ft. South of 2400 Rd.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.