

PRIMARY CORNER DESCRIPTION Sec Cor for 34 & 35; 2 & 3, T24-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2214)

Set a post 3 ft. long, 4" sq., 20" in the ground for cor. to secs. 2, 3, 34 and 35, marked T23S R3W S35 on NE.; T24S R3W S2 on SE.; T24S R3W S3 on SW.; and T23S R3W S34 on NE. faces with 2 notches on the E. and 4 notches on W. faces, from which

- A Maple 6" dia., bears S.40°W., 49 lks. dist. mkd. T24S R3W S3 BT.
- A Fir 20" dia., bears N.30°W., 44 lks. dist. mkd. T23S R3W S34 BT.
- A Fir 36" dia., bears N.15°E., 45 lks. dist. mkd. T23S R3W S35 BT.
- A Fir 36" dia., bears S.1°E., 19 lks. dist. mkd. T24S R3W S2 BT.

Weyerhaeuser Co. - June 1958 - C.S. File 53/107-14

- Found - Orig. 6" Maple, now 8" Vine Maple S.46°W., 32.3 ft. Axe marks, no scribing visible.
Orig. 20" Fir N.19°W., 29.0 ft. now snag, broken top, some scribing on bark.
Orig. 36" Fir N.46°E., 29.7 ft. most scribing visible on bark.
Orig. 36" Fir, S.5°E., 12.5 ft., scribe on bark visible.
Set 3/4" x 35" iron rod.
42" Fir S.45°W., 36.6 ft. "W" nail and plate.
50" Fir N.59°W., 51.0 ft. "W" nail and plate.
42" Fir N.46°E., 31.0 ft. "W" nail and plate. (orig BT)
52" Fir S.5°E., 10.3 ft. "W" nail and plate (Orig. BT)