

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2229)

A Fir 12" dia., which I mark ¼ S on W face for ¼ sec. cor. from which

- A Yew, 10" dia., bears S.80°W., 15 lks., mkd: ¼ S BT.
- A Fir, 12" dia., bears N.30°E., 4 lks., mkd: ¼ S BT.

Weyerhaeuser Co. 1957 thru 1963 C.S. File 53/107-17 (Feb. 1958)

Found - 12" Fir, mkd. ¼ S on W face, OK not chopped out.
10" Yew, now 24" S.80°W., 9.9 ft., OK scribing weathered off.
12" Fir, now 16" Fir snag 30' high, N.30°E., 2.6 ft., scribing ¼ on bark.

1941 record -
Brass plate on 20" Yew S.80°W., 9.9 ft. BT. Plate OK
Brass plate 16" Fir N.30°E., 2.6 ft. BT. Plate OK

BTs - 60" Fir N.51°E., 52.4 ft. "W" nail & plate.
60" Fir S.86°W., 42.9 ft. "W" nail & plate.

Dave Wellman - For: Weyerhaeuser Co. - Erin Heatherstone & Micah Johnstone - June 2003 - C.S. File 65/45-38 A&B

Found - ½" monel pipe*.
60" Fir stump, WEYCO tag reads S.51dW., 52.4 ft.
60" Fir stump, S.86°W., 42.9 ft. to face.

Set - 1¾"x36" iron pipe with 2½" brass cap dated 2003 set over top of monel pipe* - 1.2 ft. AGL

- 13" Fir S.49°E., 6.3 ft. to spike set side center - scribed "¼ S35 BT"
- 11" Fir S.33½°W., 4.4 ft. to spike set side center - scribed "¼ S34 BT"
- 13" Fir N.33°E., 32.0 ft. to spike set side center - scribed "¼ S35 BT"
- 14" Fir N.38°W., 31.2 ft. to spike set side center - scribed "¼ S34 BT"

Corner is approx. 100' North of 535 Rd.

* Monel: A trademark for a corrosion-resistant alloy of nickel & copper with some iron, manganese, & aluminum.