

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 6 Page(s) 2230)

-----

Set a post 3 ft. long 4" sq. 20" in the ground for ¼ sec. cor. mkd: ¼ on N face from which  
A Hemlock, 12" dia., bears East, 20 lks., mkd: ¼ S BT.  
A Hemlock, 30" dia., bears N.60°E., 15 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Oct. 1967 - C.S. File 54/16-27A

-----

Unrecorded 1½"x10 ft IP & new BTs.  
Weyerhaeuser method as follows:  
48" Cedar stump S.2°W., 22.6 ft. "W" Nail & tag.  
12" Yew snag N.22°W., 25.6 ft. "W" Nail & tag.  
Possible OBT  
30" Hemlock N.60°E., 9.9 ft. now only badly burned & decayed. Remains of stump - no scribe  
No trace of SE OBT.