

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 5 Page(s) 2217)

-----  
Set a post 3 ft. long 4" sq. 20" in the ground for ¼ sec. cor. mkd: ¼ on W face from which  
A Fir, 24" dia., bears West, 30 lks., mkd: ¼ S BT.  
A Fir, 30" dia., bears S.40°E., 25 lks., mkd: ¼ S BT.

Weyerhaeuser Co. 1957 thru 1963 C.S. File 53/107-15

-----  
Found - 30" Fir S.40°E., 25 lks., scribed on bark, mostly legible, face bears N.70°W.  
24" Fir W. 30 lks., 26" Fir, no scribing visible.  
Set - 3/4" x 30" Monel pipe.  
48" Fir, orig. BT, S.70°E., 16.3 ft., "W" nail & plate added.  
Fir, possible orig. BT N.70°W., 23.7 ft. no marks.  
BTs - 54" Fir N.88°W., 40.7 ft. Orig. BT "W" nail & plate added.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Nov. 1967 - C.S. File 54/16-50B

-----  
Now logged off, BTs now stumps & 5' high marker pipe alongside