

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 5 Page(s) 2217-8)

Set a basalt stone 10x8x7", 5" in the ground for cor. to secs. 25, 26, 35, & 36, mkd. with 1 notch on S & E edges from which

- A Fir, 24" dia., bears N.47°E., 60 lks., mkd: T23S R3W S25 BT.
- A Fir, 30" dia., bears S.30°E., 85 lks., mkd: T23S R3W S36 BT.
- A Fir, 28" dia., bears S.60°W., 47 lks., mkd: T23S R3W S35 BT.
- A Fir, 7" dia., bears N.55°W., 46 lks., mkd: T23S R3W S26 BT.

Corner is set beneath a stone ledge on bluff.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Nov. 1967 - C.S. File 54/16-50

Found - Orig. 24" now 38" Fir stump, N.37°E., 39.6 ft. (Rec. N.47°E.) fragmentary bark scribes. "W" nail & tag.
Orig. 30" Fir, now 48" burned stump, S.30°E., 56.1 ft. no scribe or scar. "W" nail & tag.
Orig. 28" Fir, now 42" burned stump, S.60°W., 31.0 ft., no scribe or scar. "W" nail & tag.
No trace of corner stone or NW BT.
42" Fir stump bears N.78°W. 78.0 ft. "W" nail & tag.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R3W
(set cap in mound OFFICE S 26|S 25
of stone at base of 1967 S 35|S 36
rock ledge 6 ft. high in bluff area)
No new BTs marked due to logging, no stumps other than originals.
Corner is on southerly slope of ridge sloping West.