

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 600240

PRIARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under contract #438, dated May 3, 1882 - (DCSO records Vol. 5 Page(s) 2219)

-----  
Set a post 3 ft. long 4" sq. 20" in the ground for ¼ sec. cor. mkd: ¼ on W face from which  
A Cedar, 14" dia., bears S.40°W., 12 lks., mkd: ¼ S BT.  
A Cedar, 20" dia., bears N.20°W., 25 lks., mkd: ¼ S BT.

Glen McChesney, Weyerhaeuser Co. - (Lane Co. Records) - C.S. File 53/1

-----  
GLO survey record: Post, orig. gone, found Cedar post for corner.  
14" Cedar S.40°W., 12 lks., Found  
20" Cedar N.20°W., 25 lks., Found  
Referenced by Nick Juliano Plates & "W" nail only. Decl. 20°  
26" Cedar S.69°W., 7.6 ft.  
11" Cedar N.68°E., 31.6 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Nov. 1967 - C.S. File 54/1651

-----  
Found - Squared Cedar post bears S.28°E., 4.0 ft.  
Orig. 14", now 26" Cedar, alive, S.40°W., 7.9 ft., prev. opened & shows scribe.  
Orig. 20" Cedar, now 36" stump, N.20°W., 27.0 ft. (Rec. 16.5 ft.) fragmentary scribe marks on decayed blaze.  
Set - Brass cap at cor. mkd: DOUGLAS COUNTY T23S R3W  
SURVEYORS OFFICE ¼ S 26|S 25  
1967  
New BTs- 11" Cedar N.74¼°E., 33.1 ft. mkd: "¼ S25 DCS BT"  
(Weyco ren. BT with "W" nail)  
10" Hemlock N.85°W., 33.3 ft. mkd: "¼ S26 DCS BT.  
Note - This corner lies on northerly slope on Lane-Douglas County Line.

Please note that this corner is on the Douglas Co. & Lane Co. line and Lane Co. Surveyor's Office may have more information concerning this corner.