TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 700111

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31, T23-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2185)

Set a post 4½ ft. long, and 4" sq., 24" in the ground for a closing to Ts. 23 and 24 S., R 2 W, marked C C R2W on E.; T23S S31 on N.; and T24S S6 on SE. faces, with 6 notches on NE. and S. faces, from which,

A Cedar 16" dia., bears N.9°30'E., 42 lks. dist. mkd. T23S R2W S31 BT.

A Fir 60" dia., bears S.57°E., 38 lks. dist. mkd. T24S R2W S6 BT.

An Alder 9" dia., bears S.35°W., 6 lks. dist. mkd. C C T23 and 24 S., R2W BT.

Weyerhaeuser Co. - May 1963 - C.S. File 53/106-1

Found - 16" Cedar N.9°30'E., 27.72 ft., OK, (Orig. BT)
60" Fir S.57°E., 22.9 ft., now 66" Fir stump.
No trace of 9" Alder S.35°W., 3.96 ft.
Pipe 5/8" x 2.8 for cornr.
Pipe 3/4" x 4 ft. marker.

BTs - 66" Fir stump S.58°E., 22.9 ft. (Orig. BT) "W" nail and plate.
26" Hemlock S.50°W., 18.1 ft. "W" nail and plate.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 1968 - C.S. File 54/27-217

Found - 1/2" tubing at corner and 1/2" I.P for marker with orig. BTs and "W" method BT, as recorded.
Orig. 16" now 24" Cedar stump, 5 ft. high, N.10°E., 27.7 ft., scribing visible on nearly healed blaze.
Orig. 60" Fir now 64" Fir stump, 2 ft. high, S.57°E., 25.1 ft., top of blaze visible on top of stump.
26" Hemlock stump S.50°W., 18.1 ft., "W" nail and tag.

Set Brass cap at cor. mkd: (Reset ½" tube alongside)

County Surveyors Office
T23S 3 C | S 31 R
T24S W C | S 6 2
1968 W

New BT - 9" Cedar snag, N.44°E., 28.9 ft. mkd. T23S R2W S31 CC CS BT.

Corner lies on E. side of spur, ridge sloping South about 50 ft. East of top.