

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2169)

Set a post 3 ft. long, 4" sq., 20" in the ground for ¼ sec. cor., mkd. ¼ on W. face, from which
A double Fir 70" dia., bears North, 8 lks. dist. mkd. ¼ S BT.
A Fir 36" dia., bears S.10°E., 80 lks. dist. mkd. ¼ S BT.

Find and tie above ¼ corner in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2186)

Weyerhaeuser Co. - 1957 through 1963 - C.S. File 53/107-16

Found - Double Fir, North 8 lks., scribing "BT" barely visible on bark. "X" on E. and W. side. No cruiser mark, one name.
6" Fir S.10°E., 80 lks., axe marks evident, no scribing found.
Set Cedar stake, 1/2" x 2" x 3 ft., Sept. 1957. from which
Double Fir, North 5.1 ft. (orig. BT)
46" Fir, S.4°W., 41.4 ft. (orig. BT)
BTs - 70" double Fir, SE section, snag. (Orig. BT), North 4.4 ft. "W" nail and plate.
52" I.Cedar S.75°E., 39.7 ft. "W" nail and plate.