

TOWNSHIP 23 RANGE 03 POINT IDENTIFIER # 700211

PRIMARY CORNER DESCRIPTION C.C. for Secs. 30 & 31, T23S R2W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 5 Page(s) 2186-87)

-----  
Set a basalt stone 15x10x6 ins., in the ground, for closing cor. to secs. 30 and 31, marked CC with 5 notches on N. and 1 notch on S. face, from which  
A Fir 36" dia., bears N.50°E., 37 lks. dist. mkd. T23S R2W S30 BT.  
A Fir 16" dia., bears S.40°E., 44 lks. dist. mkd. T23S R2W S31 BT.  
A Fir 24" dia., bears N.31°W., 19 lks. dist. mkd. T23S R2W CC S30 and 31 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Nov. 3, 1967 - C.S. File 54/16-50A

-----  
Found Weyerhaeuser corner with evidence of original corner. 1½" I.P. for corner and 10 ft. high marked pipe.  
Orig. 36" Fir, now 40" stump, N.50°E., 24.4 ft., cut open and face burned. No scribe.  
Orig. 16" Fir, now 17" stump, S.40°E., 29.0 ft. cut open, scribe visible.  
Orig. 24" Fir, now 30" stump, N.18°W. (Rec. N.31°W.), 12.5 ft., shows good scar. Do not open.  
Weyerhaeuser BT, 50" Fir stump, N.32°E., 4.3 ft. "W" nail and tag.  
Corner lies 75 ft. E. of spur, sloping South approx. 730 ft. N. of corner of secs. 25 and 36, T23-3W.