

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T23-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Page(s) 2332)

-----  
Set post, cor. secs. 25, 30, 31 and 36, from which  
A B.Oak 10" dia., bears S.65°W., 64 lks. dist.  
A Laurel 10" dia., bears N.45°W., 5 lks. dist.  
A Laurel 18" dia., bears N.60°E., 55 lks. dist.  
A B.Oak 15" dia., bears N.35°E., 142 lks. dist.

O.F. Thiel - For: Albert Cochran - 9/23/1926 - F.B. 116 Pg 9

-----  
At the NE. cor. of 36, Cedar post. Remarked NE tree, a Laurel SE stump bears S.29½°E. Marked Fir 18" S.44°E. 63 lks

BLM resurvey by James Jelley, under Group #895, surveyed 1976 (DCSO records Vol. 41 Page(s) 16159)

-----  
The Sec. cor., determined at record bearing and distance from the remains of the original bearing tree:

A Madrone stump 20" dia., bears N.45°W., 5 lks. dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S  
R 5 W R 4 W  
S 25 S 30  
S 36 S 31  
1976

from which new bearing trees

A Madrone 6" dia., bears N.55 3/4°E., 29 lks., mkd. T23S R4W S30 BT on bark.

A B.Oak 7" dia., bears S.53°W., 29 lks., mkd. T23S R5W S36 on bark.

A Madrone 8" dia., bears N.53°W., 2 lks., mkd. T23S R5W S25 on bark.

No other suitable trees available within limits.

Mark Smalley - For: Rsbg Resources - Oct/Nov 2002 - M137-55

-----  
Found - 1976 BLM iron pipe and brass cap

BTs - 8" Oak S.53°W., 19.1' healed

7" Madrone N.55¾°E., 19.1' down-rotten

Scribed- 8" Fir S.84°W., 9.7' "S36 BT"

8" Fir N18°E., 12,8' "S30 BT"

8" Fir S.26°E., 5.4' "S31 BT"