

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor for Sec. 7; and Sec. 12, T23-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Page(s) 2329)

Set ¼ sec. post, on top of hill, from which
A Fir 18" dia., bears N.85°E., 39 lks. dist.
A B.Oak 12" dia., bears S.37°W., 18 lks. dist.

Survey by Wilford N. Haines - For: Woolley and Whipple Mill - August 1963 - M 26-38

Found - NE BT, badly burned.
Set 1" x 1" x 36" T Iron.

Douglas Co. Surveyors Office, V. Tracy and J. Layne, crew - Oct. 27, 1965 - C.S. File 54/16-13

Found - Haines "T" Iron.
Also possible orig. BT to NE.
New BTs -10" Cedar S.7°E., 92.5 ft. mkd. ¼ S7 CS BT.
5" W.Fir N.7°W., 90.4 ft. mkd. ¼ S12 CS BT.
This corner lies on rolling East slope approx. 200.0 ft. East of top of hill.

Ken Hoffine - For: Lone Rock Timber Co. - 6/1999 - M 133-2

Found - Haines T-bar 0.5 ft. above ground on East slope approx. 120 ft. East of ridgetop.
15" I.Cedar bears S.4°E., 92.6 ft., heavy sweep tree w/BLM BT (rec. N.7°W., 92.5 ft) Well healed scar.
11" D.Fir bears N.65°W., 23.8 ft. We scribe ¼ S12 BT and tag tree.
Corner lies 85 ft. North gravel road.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 5/24/2007 - C.S. File 67/21-44

Found - 3/4" "T" iron projects 20" above ground, firmly set.
11" now 16" dia. D.Fir partially healed single blaze bears N.65°W., 23.8 ft (Agrees w/rec) 1999 BT
10" now 14" dia., x 5 ft. tall pistol butt I.Cedar, fully healed double blaze bears S.7°E., 92.5 ft. (Agrees w/DCSO 1965 rec) 1965 BT
5" now 14" dia., x 4 ft. tall rotted stump, opened to find partial scribing bears N.7°W., 90.4 ft. (agrees w/rec) 1965 BT
New - 11" dia., I.Cedar double blazed & scribed "¼ S12 CS BT" bears S.53¼°W., 33.1 ft. cont. next pg

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor for Sec. 7; and Sec. 12, T23-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

9" dia., G.Fir double blazed & scribed "¼ S7 CS BT"
bears N.43°E., 20.3 ft.
Note - Center of dirt rd. bears West 160 ft ±
Compass decl. 16¼°E.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group No. 2172 - Surveyed July/Nov. 2007 - (DCSO records Vol. 55 Page(s) 21541-2)

The ¼ sec. cor. of secs. 7 and 12, perpetuated by Haines in 1963, further perpetuated by Tracy, in 1965, further perpetuated by Hoffine in 1999, further perpetuated by Flause and Pike, in 2007, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 18" above the ground, from which the remains of an original bearing tree
A fir snag, 31" dia., bears N.85°E., 25.7 ft., with no marks visible on an opened blaze.
and bearing tree mkd. by Hoffine
A fir, 17" dia., bears N.61¼°W., 23.3 ft with healed blaze and bearing trees mkd. by Flause and Pike
A fir, 9" dia., bears N.48½°E., 20.4 ft. with scribe marks ¼ S7 CS BT visible on a partially healed double blaze
A cedar, 12" dia. bears S.58°W., 32.9 ft with scribe marks ¼ S12 CS BT visible on a partially healed double blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 21" in the ground, directly over the "T" shaped iron rod, in a mound of stone, 2 ft. base, 1½ ft. to top, with brass cap mkd.
T 23 S
R 5 W R 4 W
¼
S 12 | S 7
2007
Deposit a magnet in a white plastic case at the base of the stainless steel post.