

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

O.F. Thiel - For: Pringle Bros. - 11/1926 (recorded 9/1/1998)
- F.B. 116 Pg. 12

Set a yew post and marked:
A Fir, 12" N.32°W., 30 (lks)
A Cedar, 6" S.9°E., 19 (lks)
Note: This report was moved from T23-5 where is incorrectly placed. 1/25/2010 - JC DCSO

BLM resurvey by A. Bert Skeesick Cadastral Surveyor &
Robert H. Browning, Surveying Tech. under Group #2147,
surveyed Aug/Nov. 2006 - (DCSO rec. Vol. 55 Page(s) 21420)

Point for the center ¼ sec. cor. of sec. 19, at intersection
with the E. and W. centerline.
Set a stainless steel post, 28" long, 2½" dia., 22" in the
ground, with brass cap mkd. T23S R4W
C ¼
S 19
2006

from which
A fir, 19" dia., bears N.6¼°E., 3.8 ft., mkd. C ¼ S19 BT.
A fir, 17" dia., bears S.67¼°E., 9.3 ft., mkd. C ¼ S19 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description

Deposit a magnet in a white plastic case at the base of the
stainless steel post.