

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2313)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. mkd: ¼ S on N face, from which  
A Fir, 24" dia., bears S.46°W., 23 lks., mkd: ¼ S BT.  
A Fir, 40" dia., bears S.11°E., 55 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Stone - Jerry Layne - Oct. 1965 - C.S. File 54/16-5A

-----  
Looked for not found

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2147, surveyed Aug/Nov. 2006 - (DCSO rec. Vol. 55 Page(s) 21418)

-----  
Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. T23S R4W

¼  $\frac{S\ 18}{S\ 19}$

2006

from which

A fir, 9" dia., bears N.69¼°E., 43.6 ft., mkd. ¼ S18 BT.

A fir, 6" dia., bears S.39¼°E., 15.7 ft., mkd. ¼ S19 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located N.31°W., 15.2 ft. from a fence cor., with barbed wire fences extending E. and S.