

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wilford N. Haines - For: Woolley & Whipple Mill - Aug. 1963 - M 26-38

Set - 1" x 1" x 36" T. iron and scribed:
8" D.Fir, S.40°W., 39.4 ft.
12" D.Fir, S.80°E., 74.2 ft.

Fd. Ok 10/1979 - C.S. File 62/63-23
Fd Ok by Ken Hoffine 6/1999 M 133-2

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group No. 2172 - Surveyed July/Nov. 2007 - (DCSO records Vol. 55 Page(s) 21555)

The center ¼ sec. cor. of sec. 7, established by Haines in 1963, and is accepted as the cor., monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 6" above the ground, from which the remains of BTs mkd. by Haines

A fir, 31" dia., bears S.81¾°E., 73.2 ft., with a healed blaze.

A sawed fir stump, 12" dia., bears S.38¾°W., 39.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T 23 S R 4 W
C ¼ S 7
2007

from which a new bearing tree

A fir, 12" dia., bears N.12¼°E., 10.8 ft., mkd. C¼ S7 BT. Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description