TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Vol. 6 Page(s) 2285)

Set ¼ Sec. post from which
An Oak, 20" dia., bears S.56°W., 4 lks.
An Oak, 18" dia., bears N.55°E., 51 lks.

BLM resurvey by C. Albert White & Donald R. Beck, Cadastral Surveyors, under Group #243 & #350 - Surveyed April/June 1963 (DCSO records Vol. 32 Page(s) 13271)

The ¼ secs. cor. of secs. 31 & 32, perpetuated by persons unknown with a quarried granite stone, 16x8x6 ins. above ground, firmly set, from which the remains of the orig. BTs:
An Oak stump hole, bears N.55°E., 51 lks.
An Oak stump hole, bears S.56°W., 40 lks.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 31 S 32
T23S R4W
1963

from which new BTs:
A Cedar, 12" dia., bears N.65½°E., 355 lks., mkd: ¼ S32 BT.
A Fir, 10" dia., bears S.85°W., 235 lks., mkd: ¼ S31 BT.

Fd. & used in BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16158-59)