

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records Vol. 6 Page(s) 2286-87)

-----  
Set post cor. of secs. 19, 20, 29, & 30 from which  
A Fir, 10" dia., bears N.32°W., 19 lks.  
A Fir, 10" dia., bears S.32°W., 16 lks.  
A Fir, 20" dia., bears S.25°E., 34 lks.  
A Fir, 70" dia., bears N.55°E., 28 lks.

Fd. & used in Original GLO - William P. Wright, Deputy  
Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO  
records Vol. 6 Page(s) 2310-11)

BLM resurvey by James E. Jelley, Cadastral Surveyor, under  
Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41  
Page(s) 16161)

-----  
The cor. of secs. 19, 20, 29, & 30, determined at record  
distance from the remains of the orig. BTs:  
A Fir snag, 43" dia. bears N.58¼°E., 28 lks., with  
chaining notch visible on opened blaze. (rec. N.55°E.)  
A sawed Fir stump, 18" dia., bears S.19°E., 34 lks., with  
scribe marks S29 visible on open blaze. (rec. S.25°E.)

At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap mkd:

T23S	R4W
<u>S 19</u>	<u>S 20</u>
<u>S 30</u>	<u>S 29</u>
1976	

from which new BTs:  
A Fir, 8" dia., bears N.71 3/4°E., 68 lks., mkd: T23S R4W  
S20 BT.  
A Fir, 6" dia., bears S.19°E., 57 lks., mkd: T23S R4W S29  
BT.  
A Fir, 8" dia., bears S.7°W., 193½ lks., mkd: T23S R4W S30  
BT.  
A Fir, 16" dia., bears N.51 3/4°W., 39½ lks., mkd: T23S  
R4W S 19 BT.

Found OK by D. Baker, June 2001 - M138-71  
Fd. as per M138-71 6/2018 by D Edwards