

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page(s) 2311)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. mkd: ¼ S on W face, from which
A Fir, 40" dia., bears S.20°W., 3 lks., mkd: ¼ S BT.
A Fir, 36" dia., bears N.50°E., 37 lks., mkd: ¼ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16164-65)

From the ¼ sec. cor. of secs. 19 & 20, perpetuated by person(s) unknown, monumented with a "T" shaped iron rod, firmly set, projecting 4" above ground, from which the remains of the orig. BTs:

A Fir snag, 40" dia., bears N.50°E., 37 lks., with axe marks visible on open & burned blaze.
A Fir snag, 45" dia., bears S.20°W., 3 lks., with chaining notch visible on open and burned blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼
S 19|S 20
T23S R4W
1976

from which new BTs:

A Fir, 7" dia., bears N.35 3/4°E., 27 lks., mkd: ¼ S20 BT.
A Fir, 8" dia., bears N.35¼°W., 26 lks., mkd: ¼ S19 BT.
Reset the "T" shaped iron rod alongside iron post.

Fd. & used in BLM Resurvey, by Dale B. Bedell, Cadastral Surveyor, Surveyed under Group No. 1601. surveyed June. 1991 thru July 1992. (DCSO records Vol. 51 Page(s)19379)

David Edwards - For: Roseburg Resources - 3/2008 - M 155-14

Found - BLM Brass cap
20" fir N.35¼°W., 17.2'
Fir N.35¼°E = windfall
New BT - 9" Fir N.27°E., 3.1 ft.

continued next page

TOWNSHIP 23 RANGE 04 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2147, surveyed Aug/Nov. 2006 - (DCSO rec. Vol. 55 Page(s) 21416-7)

The ¼ sec. cor. of secs. 19 and 20, monumented with an iron post, 2½" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A decayed fir stump, 28" dia., bears N.46½°E., 26.3 ft., with no marks visible. (Record, N.50°E., 24.4 ft.)

A decayed fir stump, 44" dia., bears S.20°W., 2.0 ft., with no marks visible.

and bearing trees mkd. by Jelley in 1976

A fir, 17" dia., bears N.35¾°E., 17.8 ft., with a healed double blaze.

A fir, 21" dia., bears N.35¼°W., 17.2 ft., with a healed double blaze.