

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - William P. Wright, Deputy Surveyor, under Contract No. 514, dated Aug. 27, 1884 (DCSO records Vol. 6 Page 2314)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor. mkd: 1/4 S on N face, from which
A Fir, 24" dia., bears S.46°W., 28 lks., mkd: 1/4 S BT.
A Fir, 40" dia., bears S.11°E., 55 lks., mkd: 1/4 S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #895 - Surveyed June/Sept. 1976 (DCSO records Vol. 41 Page(s) 16167-68)

Point for 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
1/4
S 18 | S 17
T23S R4W
1976

from which
A Cedar, 12" dia., bears N.22 1/4°E., 59 lks., mkd: 1/4 S17 BT.
A Fir, 12" dia., bears N.40 1/2°W., 49 1/2 lks., mkd: 1/4 S18 BT.

Ken Hoffine, Lone Rock Timber Co. - 2/2008 - CS 65/63-8

Found - BLM brass cap set 1976 by proportion
23" Cedar bears N.22 1/4°E., 39.1 ft. (rec. N.22 1/4°E., 38.9 ft.) well healed face we re-tag.
20" D.Fir bears N.40°W., 32.7 ft (rec. N.40 1/2°W., 32.67 ft.)
Corner lies on NE slope with BLM clearcut to East flat bench approx. 120 ft. to the NE.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group No. 2172 - Surveyed July/Nov. 2007 - (DCSO records Vol. 55 Page(s) 21545-6)

The 1/4 sec. cor. of secs. 17 & 18, monumented with an iron post, 2 1/2" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.
from which bearing trees mkd. by Jelley
A cedar, 28" dia., bears N.22 1/4°E., 38.9 ft., with a healed blaze.
A fir, 20" dia., bears N.38 1/2°W., 32.7 ft., with a healed blaze. (Record, N.40 1/2°W.)